

LEGISLATIVE ACTION

Senate Comm: RCS 03/19/2015

House

- •
- •

The Committee on Transportation (Simpson) recommended the following:

Senate Amendment to Amendment (336656) (with title amendment)

Delete lines 97 - 99

and insert:

1

2

3

4 5

6 7

8

Section 41. Paragraph (b) of subsection (3) and subsection (14) of section 316.515, Florida Statutes, are amended to read: 316.515 Maximum width, height, length.-

9 (3) LENGTH LIMITATION.-Except as otherwise provided in this 10 section, length limitations apply solely to a semitrailer or



11 trailer, and not to a truck tractor or to the overall length of 12 a combination of vehicles. No combination of commercial motor 13 vehicles coupled together and operating on the public roads may 14 consist of more than one truck tractor and two trailing units. Unless otherwise specifically provided for in this section, a 15 16 combination of vehicles not qualifying as commercial motor 17 vehicles may consist of no more than two units coupled together; 18 such nonqualifying combination of vehicles may not exceed a 19 total length of 65 feet, inclusive of the load carried thereon, 20 but exclusive of safety and energy conservation devices approved 21 by the department for use on vehicles using public roads. 22 Notwithstanding any other provision of this section, a truck 23 tractor-semitrailer combination engaged in the transportation of 24 automobiles or boats may transport motor vehicles or boats on 25 part of the power unit; and, except as may otherwise be mandated 26 under federal law, an automobile or boat transporter semitrailer 27 may not exceed 50 feet in length, exclusive of the load; 28 however, the load may extend up to an additional 6 feet beyond 29 the rear of the trailer. The 50-feet length limitation does not 30 apply to non-stinger-steered automobile or boat transporters 31 that are 65 feet or less in overall length, exclusive of the 32 load carried thereon, or to stinger-steered automobile or boat 33 transporters that are 75 feet or less in overall length, 34 exclusive of the load carried thereon. For purposes of this 35 subsection, a "stinger-steered automobile or boat transporter" 36 is an automobile or boat transporter configured as a semitrailer 37 combination wherein the fifth wheel is located on a drop frame 38 located behind and below the rearmost axle of the power unit. 39 Notwithstanding paragraphs (a) and (b), any straight truck or

Page 2 of 5



40 truck tractor-semitrailer combination engaged in the 41 transportation of horticultural trees may allow the load to 42 extend up to an additional 10 feet beyond the rear of the 43 vehicle, provided said trees are resting against a retaining bar mounted above the truck bed so that the root balls of the trees 44 45 rest on the floor and to the front of the truck bed and the tops 46 of the trees extend up over and to the rear of the truck bed, 47 and provided the overhanging portion of the load is covered with protective fabric. 48

49 50 51

(b) Semitrailers.-

1. A semitrailer operating in a truck tractor-semitrailer combination may not exceed 48 feet in extreme overall outside 52 dimension, measured from the front of the unit to the rear of 53 the unit and the load carried thereon, exclusive of safety and 54 energy conservation devices approved by the department for use 55 on vehicles using public roads, unless it complies with 56 subparagraph 2. A semitrailer which exceeds 48 feet in length 57 and is used to transport divisible loads may operate in this 58 state only if issued a permit under s. 316.550 and if such 59 trailer meets the requirements of this chapter relating to 60 vehicle equipment and safety. Except for highways on the tandem 61 trailer truck highway network, public roads deemed unsafe for 62 longer semitrailer vehicles or those roads on which such longer 63 vehicles are determined not to be in the interest of public 64 convenience shall, in conformance with s. 316.006, be restricted 65 by the Department of Transportation or by the local authority to 66 use by semitrailers not exceeding a length of 48 feet, inclusive 67 of the load carried thereon but exclusive of safety and energy conservation devices approved by the department for use on 68

TR.TR.02552

73

74

75

76

77

78

80

81 82

83

84

86 87

88 89 90



69 vehicles using public roads. Truck tractor-semitrailer 70 combinations shall be afforded reasonable access to terminals; facilities for food, fuel, repairs, and rest; and points of 71 72 loading and unloading.

2. A semitrailer which is more than 48 feet but not more than 57 53 feet in extreme overall outside dimension, as measured pursuant to subparagraph 1., may operate on public roads, except roads on the State Highway System which are restricted by the Department of Transportation or other roads restricted by local authorities, if:

79 a. The distance between the kingpin or other peg that locks into the fifth wheel of a truck tractor and the center of the rear axle or rear group of axles does not exceed 41 feet, or, in the case of a semitrailer used exclusively or primarily to transport vehicles in connection with motorsports competition events, the distance does not exceed 46 feet from the kingpin to 85 the center of the rear axles; and

b. It is equipped with a substantial rear-end underride protection device meeting the requirements of 49 C.F.R. s. 393.86, "Rear End Protection."

91 And the title is amended as follows: 92 93 Delete line 981 94 and insert: 95 316.515, F.S.; extending the allowable length of certain semitrailers authorized to operate on public 96 97 roads under certain conditions; authorizing the

Page 4 of 5

TR.TR.02552

391500

98

Department