

	LEGISLATIVE ACTION	
Senate		House
	•	
	•	
Floor: 1b/RE/3R	•	
03/11/2016 01:35 PM	•	
	•	

Senator Simpson moved the following:

Senate Amendment to Amendment (691108) (with title amendment)

3 4

6

8

9

10 11

1

Between lines 747 and 748

5 insert:

> Section 8. Paragraph (b) of subsection (3) of section 316.515, Florida Statutes, is amended to read:

316.515 Maximum width, height, length.

(3) LENGTH LIMITATION.—Except as otherwise provided in this section, length limitations apply solely to a semitrailer or trailer, and not to a truck tractor or to the overall length of

12

13

14

15

16 17

18 19

2.0

21

22 23

24

25

26

27

28

29

30

31 32

33

34

35

36

37

38

39

40



a combination of vehicles. No combination of commercial motor vehicles coupled together and operating on the public roads may consist of more than one truck tractor and two trailing units. Unless otherwise specifically provided for in this section, a combination of vehicles not qualifying as commercial motor vehicles may consist of no more than two units coupled together; such nonqualifying combination of vehicles may not exceed a total length of 65 feet, inclusive of the load carried thereon, but exclusive of safety and energy conservation devices approved by the department for use on vehicles using public roads. Notwithstanding any other provision of this section, a truck tractor-semitrailer combination engaged in the transportation of automobiles or boats may transport motor vehicles or boats on part of the power unit; and, except as may otherwise be mandated under federal law, an automobile or boat transporter semitrailer may not exceed 50 feet in length, exclusive of the load; however, the load may extend up to an additional 6 feet beyond the rear of the trailer. The 50-feet length limitation does not apply to non-stinger-steered automobile or boat transporters that are 65 feet or less in overall length, exclusive of the load carried thereon, or to stinger-steered automobile or boat transporters that are 75 feet or less in overall length, exclusive of the load carried thereon. For purposes of this subsection, a "stinger-steered automobile or boat transporter" is an automobile or boat transporter configured as a semitrailer combination wherein the fifth wheel is located on a drop frame located behind and below the rearmost axle of the power unit. Notwithstanding paragraphs (a) and (b), any straight truck or truck tractor-semitrailer combination engaged in the



transportation of horticultural trees may allow the load to extend up to an additional 10 feet beyond the rear of the vehicle, provided said trees are resting against a retaining bar mounted above the truck bed so that the root balls of the trees rest on the floor and to the front of the truck bed and the tops of the trees extend up over and to the rear of the truck bed, and provided the overhanging portion of the load is covered with protective fabric.

(b) Semitrailers.-

41 42

43

44

45

46

47

48 49

50

51

52

53

54

55

56

57

58

59

60

61 62

63

64 65

66

67

68

69

1. A semitrailer operating in a truck tractor-semitrailer combination may not exceed 48 feet in extreme overall outside dimension, measured from the front of the unit to the rear of the unit and the load carried thereon, exclusive of safety and energy conservation devices approved by the department for use on vehicles using public roads, unless it complies with subparagraph 2. A semitrailer which exceeds 48 feet in length and is used to transport divisible loads may operate in this state only if issued a permit under s. 316.550 and if such trailer meets the requirements of this chapter relating to vehicle equipment and safety. Except for highways on the tandem trailer truck highway network, public roads deemed unsafe for longer semitrailer vehicles or those roads on which such longer vehicles are determined not to be in the interest of public convenience shall, in conformance with s. 316.006, be restricted by the Department of Transportation or by the local authority to use by semitrailers not exceeding a length of 48 feet, inclusive of the load carried thereon but exclusive of safety and energy conservation devices approved by the department for use on vehicles using public roads. Truck tractor-semitrailer



combinations shall be afforded reasonable access to terminals; facilities for food, fuel, repairs, and rest; and points of loading and unloading.

- 2. A semitrailer which is more than 48 feet but not more than $57 \frac{53}{5}$ feet in extreme overall outside dimension, as measured pursuant to subparagraph 1., may operate on public roads, except roads on the State Highway System which are restricted by the Department of Transportation or other roads restricted by local authorities, if:
- a. The distance between the kingpin or other peg that locks into the fifth wheel of a truck tractor and the center of the rear axle or rear group of axles does not exceed 41 feet, or, in the case of a semitrailer used exclusively or primarily to transport vehicles in connection with motorsports competition events, the distance does not exceed 46 feet from the kingpin to the center of the rear axles; and
- b. It is equipped with a substantial rear-end underride protection device meeting the requirements of 49 C.F.R. s. 393.86, "Rear End Protection."

89

======= T I T L E A M E N D M E N T =========

And the title is amended as follows:

Delete line 3164

and insert: 93

70

71

72 73

74

75

76 77

78

79

80

81

82

83

84

85

86

87 88

90

91

92

94

95

96

97

in vehicles; amending s. 316.515, F.S.; extending the allowable length of certain semitrailers authorized to operate on public roads under certain conditions; amending s. 316.640, F.S.; expanding the