1

1 2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

| ADOPTED               | (Y/N) |
|-----------------------|-------|
| ADOPTED AS AMENDED    | (Y/N) |
| ADOPTED W/O OBJECTION | (Y/N) |
| FAILED TO ADOPT       | (Y/N) |
| WITHDRAWN             | (Y/N) |
| OTHER                 |       |

Committee/Subcommittee hearing bill: State Affairs Committee Representative Payne offered the following:

Amendment (with title amendment)

Between lines 198 and 199, insert:

Section 6. Subsections (3) and (4) of section 316.515, Florida Statutes, are amended, and subsection (16) is added to that section, to read:

316.515 Maximum width, height, length.

(3) LENGTH LIMITATION.—Except as otherwise provided in this section, length limitations apply solely to a semitrailer or trailer, and not to a truck tractor or to the overall length of a combination of vehicles. No combination of commercial motor vehicles coupled together and operating on the public roads may consist of more than one truck tractor and two trailing units. Unless otherwise specifically provided for in this section, a

717303 - h0725-line198.docx

17

18

19

20

21

22

23

24

25

2627

28

29

30

31

32

33

34

35

36

37

38

39

40 41

```
combination of vehicles not qualifying as commercial motor
vehicles may consist of no more than two units coupled together;
such nonqualifying combination of vehicles may not exceed a
total length of 65 feet, inclusive of the load carried thereon,
but exclusive of safety and energy conservation devices approved
by the department for use on vehicles using public roads.
Notwithstanding any other provision of this section, a truck
tractor-semitrailer combination engaged in the transportation of
automobiles or boats may transport motor vehicles or boats on
part of the power unit; and, except as may otherwise be mandated
under federal law, an automobile or boat transporter semitrailer
may not exceed 50 feet in length, exclusive of the load;
however, the load may extend up to an additional 6 feet beyond
the rear of the trailer. The 50-feet length limitation does not
apply to non-stinger-steered automobile or boat transporters
that are 65 feet or less in overall length, exclusive of the
load carried thereon, or to stinger-steered automobile or boat
transporters that are 75 feet or less in overall length,
exclusive of the load carried thereon, or to stinger-steered
automobile transporters that are 80 feet or less in overall
length, exclusive of the load carried thereon. For purposes of
this subsection, a "stinger-steered automobile or boat
transporter" is an automobile or boat transporter configured as
a semitrailer combination wherein the fifth wheel is located on
a drop frame located behind and below the rearmost axle of the
```

717303 - h0725-line198.docx

 power unit. Automobile transporters operating under this subsection may backhaul cargo or general freight if the weight of such cargo or freight does not exceed the limits imposed under s. 316.535. Notwithstanding paragraphs (a) and (b), any straight truck or truck tractor-semitrailer combination engaged in the transportation of horticultural trees may allow the load to extend up to an additional 10 feet beyond the rear of the vehicle, provided the said trees are resting against a retaining bar mounted above the truck bed so that the root balls of the trees rest on the floor and to the front of the truck bed and the tops of the trees extend up over and to the rear of the truck bed, and provided the overhanging portion of the load is covered with protective fabric.

(a) Straight trucks.—A straight truck may not exceed a length of 40 feet in extreme overall dimension, exclusive of safety and energy conservation devices approved by the department for use on vehicles using public roads. A straight truck may attach a forklift to the rear of the cargo bed, provided the overall combined length of the vehicle and the forklift does not exceed 50 feet. Except as otherwise provided in this section, a straight truck may tow no more than one trailer, and the overall length of the truck-trailer combination may not exceed 68 feet, including the load thereon.

Notwithstanding any other provisions of this section, a truck-trailer combination engaged in the transportation of boats, or

717303 - h0725-line198.docx

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90 91 boat trailers whose design dictates a front-to-rear stacking method may not exceed the length limitations of this paragraph exclusive of the load; however, the load may extend up to an additional 6 feet beyond the rear of the trailer.

## (b) Semitrailers.-

A semitrailer operating in a truck tractor-semitrailer combination may not exceed 48 feet in extreme overall outside dimension, measured from the front of the unit to the rear of the unit and the load carried thereon, exclusive of safety and energy conservation devices approved by the department for use on vehicles using public roads, unless it complies with subparagraph 2. A semitrailer which exceeds 48 feet in length and is used to transport divisible loads may operate in this state only if issued a permit under s. 316.550 and if such trailer meets the requirements of this chapter relating to vehicle equipment and safety. Except for highways on the tandem trailer truck highway network, public roads deemed unsafe for longer semitrailer vehicles or those roads on which such longer vehicles are determined not to be in the interest of public convenience shall, in conformance with s. 316.006, be restricted by the Department of Transportation or by the local authority to use by semitrailers not exceeding a length of 48 feet, inclusive of the load carried thereon but exclusive of safety and energy conservation devices approved by the department for use on vehicles using public roads. Truck tractor-semitrailer

717303 - h0725-line198.docx

combinations shall be afforded reasonable access to terminals; facilities for food, fuel, repairs, and rest; and points of loading and unloading.

- 2. A semitrailer which is more than 48 feet but not more than 57 feet in extreme overall outside dimension, as measured pursuant to subparagraph 1., may operate on public roads, except roads on the State Highway System which are restricted by the Department of Transportation or other roads restricted by local authorities, if:
- a. The distance between the kingpin or other peg that locks into the fifth wheel of a truck tractor and the center of the rear axle or rear group of axles does not exceed 41 feet, or, in the case of a semitrailer used exclusively or primarily to transport vehicles in connection with motorsports competition events, the distance does not exceed 46 feet from the kingpin to the center of the rear axles; and
- b. It is equipped with a substantial rear-end underride protection device meeting the requirements of 49 C.F.R. s. 393.86, "Rear End Protection."
  - (c) Tandem trailer trucks.-
- 1. Except for semitrailers and trailers of up to 28 1/2 feet in length which existed on December 1, 1982, and which were actually and lawfully operating on that date, no semitrailer or trailer operating in a truck tractor-semitrailer-trailer combination may exceed a length of 28 feet in extreme overall

717303 - h0725-line198.docx

outside dimension, measured from the front of the unit to the rear of the unit and the load carried thereon, exclusive of safety and energy conservation devices approved by the Department of Transportation for use on vehicles using public roads.

- 2. Tandem trailer trucks conforming to the weight and size limitations of this chapter and in immediate transit to or from a terminal facility as defined in this chapter may operate on the public roads of this state except for residential neighborhood streets restricted by the Department of Transportation or local jurisdictions. In addition, the Department of Transportation or local jurisdictions may restrict these vehicles from using streets and roads under their maintenance responsibility on the basis of safety and engineering analyses, provided that the restrictions are consistent with the provisions of this chapter. The Department of Transportation shall develop safety and engineering standards to be used by all jurisdictions when identifying public roads and streets to be restricted from tandem trailer truck operations.
- 3. Except as otherwise provided in this section, within 5 miles of the Federal National Network for large trucks, tandem trailer trucks shall be afforded access to terminals; facilities for food, fuel, repairs, and rest; and points of loading and unloading.

717303 - h0725-line198.docx

- 4. Notwithstanding the provisions of any general or special law to the contrary, all local system tandem trailer truck route review procedures must be consistent with those adopted by the Department of Transportation.
- 5. Tandem trailer trucks employed as household goods carriers and conforming to the weight and size limitations of this chapter shall be afforded access to points of loading and unloading on the public streets and roads of this state, except for streets and roads that have been restricted from use by such vehicles on the basis of safety and engineering analyses by the jurisdiction responsible for maintenance of the streets and roads.
- (d) Maxi-cube vehicles.—Maxi-cube vehicles shall be allowed to operate on routes open to tandem trailer trucks under the same conditions applicable to tandem trailer trucks as specified by this section.
- (4) LOAD EXTENSION LIMITATION.—The load upon any vehicle operated alone, or the load upon the front vehicle of a combination of vehicles, may not extend more than 3 feet beyond the front wheels of the vehicle or the front bumper of the vehicle if it is equipped with a bumper. However, the load upon any stinger-steered automobile transporter may not extend more than 4 feet beyond the front bumper of the vehicle.

| 165 | (a) The limitations of this subsection do not apply to                                  |
|-----|---|
| 166 | bicycle racks carrying bicycles on public sector transit                                |
| 167 | vehicles.   |
| 168 | (b) <del>The provisions of</del> This subsection <u>does</u> <del>shall</del> not apply |
| 169 | to a front-end loading collection vehicle, when:  |
| 170 | 1. The front-end loading mechanism and container or                                     |
| 171 | containers are in the lowered position;   |
| 172 | 2. The vehicle is engaged in collecting solid waste or                                  |
| 173 | recyclable or recovered materials;  |
| 174 | 3. The vehicle is being operated at speeds less than 20                                 |
| 175 | miles per hour with the vehicular hazard-warning lights                                 |
| 176 | activated; and  |
| 177 | 4. The extension does not exceed 8 feet 6 inches.                                       |
| 178 | (16) TOWAWAY TRAILER TRANSPORTER COMBINATIONS.—An unladen                               |
| 179 | power unit may tow two trailers or semitrailers when the                                |
| 180 | combination is not used to carry property, the overall                                  |
| 181 | combination length does not exceed 82 feet, and the total gross                         |
| 182 | weight of the combination does not exceed 26,000 pounds. The                            |
| 183 | trailers or semitrailers must constitute inventory property of a                        |
| 184 | manufacturer, distributor, or dealer of such trailers or                                |
| 185 | semitrailers.   |
| 186 |   |
| 187 |   |

717303 - h0725-line198.docx

188

189

Published On: 3/27/2019 5:40:17 PM

Remove line 30 and insert:

TITLE AMENDMENT

## COMMITTEE/SUBCOMMITTEE AMENDMENT Bill No. CS/HB 725 (2019)

Amendment No.

| 190 | video; amending s. 316.515, F.S.; revising length and load     |
|-----|--|
| 191 | extension limitations for stinger-steered automobile           |
| 192 | transporters; authorizing automobile transporters to backhaul  |
| 193 | certain cargo or freight under certain circumstances;          |
| 194 | authorizing an unladen power unit to tow a certain combination |
| 195 | of trailers or semitrailers under certain circumstances;       |
| 196 | amending s. 320.01, F.S.; revising the                         |

717303 - h0725-line198.docx